



AVCOMM®

6006GX2-POE Datasheet

Aiming to create better and safer working environments and life experiences through the products we deliver.



AVCOMM Technologies, Inc

www.avcomm.us

Email: info@avcomm.us

Phone: (713) 933-4534

Address: 333 West Loop North, Suite 460
Houston, TX 77024
United States

Building More Powerful Industrial POE Aggregation Network

6006GX2-POE

Industrial 4G+2G SFP Managed PoE Switch

6006GX2-POE is an industrial L2 smart managed PoE switch. Equipped with 4 Gigabit PoE af/at ports and 2 100M/1000M SFP fiber ports. The 4 Gigabit PoE/PoE+ ports can feed IP cam or wireless AP up to 30W/port. The 6006GX2-POE designs with the latest ERPS v2 ring which is fully compatible with 3rd party devices for flexible network upgrade. The USB port for configuration file can help mass installation and site support. Wide operating temperature design (-40~75°C) can withstand critical industrial environment. All switches pass 4 hours 60°C stress test before delivery to ensure utmost quality. The ANMS supports network management for up to 2000 nodes.



High Throughput Ethernet Switching

- 4 Gigabit Ethernet port and 2 Giga SFP slots
- 8K MAC address table
- Stores and Forwards with non-blocking Switch Fabric

ITU-T G.8032 v1/v2 ERPS Ring Redundancy

- An ITU standard Ring redundancy Protocol
- Provide sub-50ms protection and recovery switching for Ethernet traffic
- Interoperate with 3rd party industrial switch and still remain fast recovery time
- Interoperate with commercial switch instead of STP/RSTP
- Efficient network interconnection with ERPS Chain, multiple chain

Smart Management

- Supports web pages, command lines, Telnet, SNMP v1/v2c/v3/trap
- LLDP topology control
- USB for easy field side configuration and firmware update
- ANMS - NMS system surveillance by individual nodes
- AIAS - remote configuration software for distributed management

Extreme PoE Capability

- 4-port provide IEEE 802.3af/at compliance PoE, up to 30W per port
- Up to 120W PoE power budget
- Complete PoE management including per-port Power Budget Control, PoE Scheduling and PoE Status

IEC62443-4-2 Level 3/4 Cyber Security

- 802.1Q VLAN, private VLAN, advanced port security
- L2-L7 IPv4/IPv6 Access Control List (ACL)
- DHCP Snooping, IP Source Guard, Dynamic ARP Inspection
- Multi-level user authentication
- HTTPS/SSH/SFTP, 256-bit AES encryption
- 802.1x MAB for non-802.1x compliant end device connection authentication
- RADIUS/TACACS+ Centralized Password Authentication

Rugged Design for Security Surveillance

- Rugged design prevents mechanical deformation
- Wide operating temperature range: -40~75°C, humidity: 95%
- Wide operating voltage range: 46~57VDC
- IEC61000-6-2/4 heavy industrial EMC

PoE (Power Over Ethernet) Details	PoE (IEEE 802.3af)	PoE+ (IEEE 802.3at)
Max power	15.40 W	34.20 W
Available power for the device	12.95 W	25.50 W
Voltage output range	44-58 VDC	50-57 VDC
Max output current	350 mA	600 mA
Power management level	L3	L4



Ordering Information

Model Name	Description
6006GX2-POE	6-Port Industrial Fully Managed POE Switch, 4 RJ45 10/100/1000BaseT(X), 2 SFP Slots 1000BaseSFP+, Support POE/POE+, Support ITU-TG.8032, DIN-Rail, Dual Power Input 46-57VDC, -40°C-75°C
6006GX2-POE-2SX	6006GX2-POE, w/ 2 AVC-SFP-SX
6006GX2-POE-2LX-10	6006GX2-POE, w/ 2 AVC-SFP-LX-10
6006GX2-POE-2LX-40	6006GX2-POE, w/ 2 AVC-SFP-LX-40
6006GX2-POE-PS	6006GX2-POE, w/ 1 APS-240-48
6006GX2-POE-2SX-PS	6006GX2-POE, w/ 1 APS-240-48 and 2 AVC-SFP-SX
6006GX2-POE-2LX-10-PS	6006GX2-POE, w/ 1 APS-240-48 and 2 AVC-SFP-LX-10
6006GX2-POE-2LX-40-PS	6006GX2-POE, w/ 1 APS-240-48 and 2 AVC-SFP-LX-40

Technology	
Standard	IEEE 802.3 10Base-T Ethernet
	IEEE 802.3u 100Base-TX Fast Ethernet
	IEEE 802.3ab 1000Base-T Gigabit Ethernet copper
	IEEE 802.3u 100Base-FX Fast Ethernet Fiber
	IEEE 802.3x Flow Control and back-pressure
	IEEE 802.3ab 1000Base-T Gigabit Ethernet copper
	IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
	IEEE 802.1p Class of Service (CoS)
	IEEE 802.1Q VLAN
	ITU-T G.8032 Ethernet ring protection switching (ERPS)
	IEEE 802.1D-2004 Rapid Spanning Tree Protocol (RSTP)
	IEEE 1588 Precision Time Protocol v1/2
	Interface
Ethernet Port	4 x 100/1000MBase-T RJ45, Auto Negotiation 2 x 100/1000M SFP
System LED	2 x Power: Green On 1x SYS: Ready: (Green On), Firmware Updating: (Green Blinking) 1 x DO: Red On 2 x Fiber: Link (Green On), Activity (Green Blinking) 1 x Ring: Off: Ring disabled, Green On: Ring normal (Not RPL Owner), Green Blinking: Ring normal (RPL Owner) 4 x PoE status: Green On
Ethernet Port LED	Link (Green On), Activity (Green Blinking)
Reset	System Reset(2~6 Seconds) / Default Settings Reset(over 7 Seconds)
USB	1 x USB for Configuration/Firmware Update
Power Input, Digital Output	6-Pin Removable Terminal Block Connector 4 Pin for Redundant Power 2 Pin for DO (Relay Alarm) DO: Dry Relay Output with 0.5A/24V DC
Power Requirement	
Input Voltage	48VDC(46~57VDC, 50~57VDC suggested for IEEE802.3at)
Reverse Polarity Protect	Yes
Input Current	2.5A@54VDC
Power Consumption	Max 8.5W@54VDC full traffic without PD Loading, suggest to reserve 15% tolerance
Software	
Management Interface	CGI WebGUI, Command Line Interface (CLI), Telnet, SNMP
Time Management	NTP, *IEEE 1588 Precision Time Protocol v1/2
Network Management	IPv4, SNMP v1/v2c/v3/Trap, MIBs, LLDP, DHCP server/client, TFTP, System Log, SMTP
Traffic Management	Flow Control, VLAN, Class of Service, QOS, Rate Control, Port Mirror
Security	Management IP, SSH, SSL
Redundancy	Rapid Spanning Tree Protocol (RSTP) ITU-T G.8032 v1/v2 Ethernet Ring Protection Switching (ERPS)

PoE	
Power forwarding mode	Alternative A
PoE Power Budget	System:Max.120W@75°C Per Port: Max. 30W
PoE Standard	IEEE 802.3af/at
Management	System/Port Power Budget Control, PD Alive Check, PoE Scheduling, PoE Status
Mechanical	
Installation	DIN Rail
Enclosure Material	Steel Metal with Aluminum
Dimension	78.5 mm x 149 mm x 125 mm(W x H x D) / without DIN Rail Clip
Ingress Protection	IP31
Weight	Around 800g
Environmental	
Operating Temperature & Humidity	-40°C~75°C , 5%~95% Non- Condensing
Storage Temperature	-40°C~85°C
MTBF	>2,000,000 hours
Warranty	5 years
Standard	
Safety	EN60950-1 Compliance
EMC	EN61000-6-2/EN61000-6-4
EMI	CISPR 22, FCC part 15B Class A
EMS	EN61000-4-2 ESD, EN61000-4-3 RS, EN61000-4-4 EFT, EN61000-4-5, EN61000-4-6 CS, EN61000-4-8 Magnetic Field



function interface

System LED

- 2 x Power
- 1 x System Status
- 1 x DO
- 2 x Fiber Port
- 1 x Ring
- 4 x PoE

Gigabit Ethernet

- 4 x 100/1000M RJ45
- IEEE 802.3af/at

Fiber Ethernet

- 2 x 100M/1000M SFP

Easy System Management

- USB for Configuration/
Firmware update

DIN Clip

Integrated Power Connector

- 1 x 6-pin terminal block
4 pin for redundant power input
2 pin DO



Installation dimensions

Unit: $\frac{\text{inch} \pm 0.040}{[\text{mm}] \pm 1.00}$

