



AVCOMM®

8028GX8

Datasheet

Aiming to create better and safer working environments and life experiences through the products we deliver.



AVCOMM Technologies, Inc

www.avcomm.us

Email: info@avcomm.us

Phone: (713) 933-4534

Address: 333 West Loop North, Suite 460
Houston, TX 77024
United States

Rackmount Ruggedized 28G Layer 2 Switch with Cyber Security and Cloud Management

8028GX8

Industrial 28G L2 Rackmount Managed Ethernet Switch

8028GX8 is a power substation compliant rackmount 28G switch with 20 Giga copper ports, 4 Giga combo ports and 4x100M/1G/2.5G fiber SFP ports. Up to 8 fiber Giga ports help to link more field switches with long distance fiber connections. The 28 full giga ports enhance the overall throughput for industrial control room applications. Rugged design and high EMC immunity makes 8028GX8 an ideal solution for roadside and power substation applications.



High Throughput Ethernet Switching

- 28-port Full GbE, by 24-port GbE RJ45 and 4-port GbE RJ45/SFP Combo, and 4 100M/1G/2.5G SFP fiber ports
- Up to 24 GbE copper RJ-45 ports
- Up to 8 100M/1G/2.5GbE fiber ports add more fiber links to field switches
- DDM function for high quality fiber connectivity monitoring Powerful 1.2GHz ARM Cotex-A9 processor
- Less than 12.5W power consumption at full loading
- Energy-Efficient Ethernet for power saving
- Non-blocking switch fabric design
- 8 flexible Class of Service(CoS) queues, 512 L2 Multicast Groups for video applications
- 16K MAC address table, 9Kb Jumbo Frame

ITU-T G.8032 v2 ERPS Ring Redundancy

- ITU-T G.8032 v1/v2 ERPS Standard Ring Redundancy protocol
- Supports HW-based CFM transmission for overcoming GbE copper physical limitation and providing minimum 20ms recovery time, seamless restoration time
- Inter-Operability with 3rd party industrial switch and still remain fast recovery time
- Replace Ring + Chain + Dual Homing

Enhanced RSTP(eRSTP)

- Enhance the RSTP fault recovery time performance
- Enhance RSTP performance for large ring network topologies with up to 80 switches

IEC62443-4-2 Level 3 / 4 Cyber Security

- L2-L7 IPv4/IPv6* Access Control List (ACL)
- DHCP Snooping, IP Source Guard, Dynamic ARP Inspection
- 802.1Q VLAN, Private VLAN, Advanced Port Security
- Multi-Level user passwords
- HTTPS/SSH/SFTP, 256-bit encryption
- 802.1X MAB for non-802.1X compliant end devices
- RADIUS/TACACS+ centralized password authentication

Industrial IoT LAN & Cloud Management

- Various configuration paths, including CGI WebGUI, CLI, SNMP and RMON
- Support AVCOMM Software Utilities:
 - ANMS Network Management System
 - AIAS for Configuration Management
 - ANMS*, ATMS OTA* for device management over Cloud*
- Support MQTT* protocol, ready to use AWS/Azure and Private Cloud Agent for cloud management
- LLDP for topology control, auto-topology drawing
- USB for easy field configuration and firmware update

Rugged Design for Industrial Control Room and Wayside Network Switching

- IEC61850-3/IEEE1613 compliance for power substation applications
- Seamless forwarding while EMC attack*
- Excellent heat dissipation design for operating in -40~75°C environments
- High level EMC protection exceeding traffic control and heavy industrial standards' requirements
- EN50121-4 railway trackside EMC
- IEC 61000-6-2/4 Heavy Industrial Environment



Ordering Information

Model Name	Description
8028GX8-AC2	28-Port Fully Managed Industrial Ethernet Switch, 24 RJ45 Ports 10/100/1000Base-T(X), 4 Combo Ports (10/100/1000BaseT(X) or 100/1000BaseSFP+), 4 Slots 1000BaseSFP+, Rack Mounting, Dual Power Input 90-264VAC, -40°C-75°C
8028GX8-AC2-2SX	8028GX8-AC2, w/ 2 AVC-SFP-SX
8028GX8-AC2-2LX-10	8028GX8-AC2, w/ 2 AVC-SFP-LX-10
8028GX8-AC2-2LX-40	8028GX8-AC2, w/ 2 AVC-SFP-LX-40
8028GX8-AC2-4SX	8028GX8-AC2, w/ 4 AVC-SFP-SX
8028GX8-AC2-4LX-10	8028GX8-AC2, w/ 4 AVC-SFP-LX-10
8028GX8-AC2-4LX-40	8028GX8-AC2, w/ 4 AVC-SFP-LX-40
8028GX8-AC2-6SX	8028GX8-AC2, w/ 6 AVC-SFP-SX
8028GX8-AC2-6LX-10	8028GX8-AC2, w/ 6 AVC-SFP-LX-10
8028GX8-AC2-6LX-40	8028GX8-AC2, w/ 6 AVC-SFP-LX-40
8028GX8-AC2-8SX	8028GX8-AC2, w/ 8 AVC-SFP-SX
8028GX8-AC2-8LX-10	8028GX8-AC2, w/ 8 AVC-SFP-LX-10
8028GX8-AC2-8LX-40	8028GX8-AC2, w/ 8 AVC-SFP-LX-40

Technology	
Standard	IEEE 802.3 10Base-T Ethernet
	IEEE 802.3u 100Base-TX Fast Ethernet
	IEEE 802.3u 100Base-FX Fast Ethernet Fiber
	IEEE 802.3ab 1000Base-T Gigabit Ethernet copper
	IEEE 802.3z Gigabit Ethernet Fiber
	IEEE 802.3x Flow Control and back-pressure
	IEEE 802.3az (Energy Efficient Ethernet)
	IEEE 802.1p Class of Service (CoS)
	IEEE 802.1Q VLAN and GVRP
	IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
	IEEE 802.1D-2004 Rapid Spanning Tree Protocol (RSTP)
	IEEE 802.1S Multiple Spanning Tree Protocol (MSTP)
	IEEE 801.1AX/802.3ad Link Aggregation Control Protocol (LACP)
	IEEE 802.1x Port based Network Access Protocol
	IEEE 1588 Precision Time Protocol v2
ITU-T G.8032 version 2 Ethernet ring protection switching(ERPSv2)	
Performance & Scalability	
Switch Technology	Store and Forward Technology with 56Gbps Non-Blocking Switch Fabric Internal Packet Buffer: 4Mb Forwarding rate: 41.67Mpps (1,488,000pps/port)
CPU	Cortex-A9, max. 1.2GHz
RAM	DDR3 2Gb
Number of MAC Address	16K
Jumbo Frame	9216 Bytes
VLAN	256 VLANs, VLAN ID 1~4094
IGMP Groups	512
Traffic Prioritize	8 Priority Queues per Port
Interface	
Ethernet Port	24 x 10/100/1000M RJ45, Auto Negotiation 4 x 100/1000M RJ45/SFP Combo, Auto Negotiation, 4 x 100/1000M SFP, DDM Energy-Efficient Ethernet for power saving
System LED	2 x Power (P1/P2): Green On 1 x System Status: Ready: Green On, Firmware Updating: Green Blinking 1 x DI: Green On, 1 x Alarm: Red On 1 x Ring Status: Node Normal: Green On, Owner Normal: Green Blinking, Owner/Node Abnormal: Amber On, Ring Port Fail: Amber Blinking
Giga Ethernet Port LED	Link (Green On), Activity (Green Blinking), Speed 1000M(Amber On), Speed 10M/100M (Amber Off)
Giga SFP LED	Port: Link (Green On), Activity (Green Blinking) 1000M: Speed 1000M (Amber On), Speed 100M (Off)
Console	1 x RJ45 based RS232 for System Configuration. Baud Rate: 115200.n.8.1
USB	1 x USB for Configuration/Firmware Update

Digital Output (Alarm)	1x Digital Output: Dry Relay Output with 0.5A/24V DC
Digital Input	1x Digital Input. Low: 0~10V, High: 11~30V
Watchdog	Hardware-based 10 seconds timer
Power Requirement	
Operating Voltage	Power Input: AC110/220V (90-264VAC), 88~300VDC 2AC: Dual AC110/220V (90-264VAC), 88~300VDC DC Input: 48V (DC Model only, Other DC Input Range By Request)
Power Consumption	Max. 20W @ 8x SFP plugged
Software	
Management	CGI WebGUI, Command Line Interface (CLI), IPv4/IPv6(RFC2460), Telnet, SNMP v1/v2c/v3, SNMP Trap/Informs*, RMON, LLDP, DHCP server/client/Option 82, TFTP, System Log, SMTP
Traffic Management	Flow Control, Rate Control, Port Mirror, CoS, QoS, RFC 2474 DiffServ
Filter	IGMP Snooping v1/v2/v3, IGMP Snooping Fast-Leave/Immediate-Leave, IGMP Query, GMRP, IEEE802.1Q VLAN, QinQ, GVRP, Private VLAN, IGMP Query Solicitation/Request*, MLDv1/v2 Snooping*, IEEE 802.1v*
Security	IEEE 802.1X/RADIUS, TLS v1.2, HTTPS/SSH
Advanced Security	TACACS+, Multi-user authentication, IEEE802.1x MAB, DHCP Snooping/IPSG, Dynamic ARP inspection, DoS/DDoS*, Adv. Port security*, SFTP
Redundancy	ERPSv2 (HW-based CFM), STP/RSTP/MSTP, eRSTP, Loop Protection*, Port Trunk/801.1AX/802.3ad LACP
Time Management	NTP, IEEE 1588 Precision Time Protocol v2
IIoT Industrial Protocol	Modbus TCP, EtherNet/IP*, MQTT*, RESTful API*
Private Cloud	ATMS*, ATMS OTA*
Public Cloud	AWS Agent*, Azure Agent*
Utility	AIAS, ANMS
MIB	ERPS MIB, MIB-II, Ethernet-like MIB*, P-BRIDGE MIB, Q-BRIDGE MIB, Bridge MIB, RMON MIB Group 1, 2, 3, 9*, AVCOMM Private MIB
Mechanical	
Installation	Rackmount
Enclosure Material	Steel Metal
Dimension	RS628v2: 431 mm x 44 mm x 170 mm(W x H x D) RS628v2-2AC/AC+DC: 431 x 44 x 300 mm(W x H x D)
Ingress Protection	IP40
Weight	≈2.5KG (full package)
Environmental	
Operating Temperature & Humidity	-40°C~75°C , 0%~95% Non- Condensing
Storage Temperature	-40°C~85°C
MTBF	>2,000,000 hours
Warranty	5 years

Standard		
EMI	CISPR 22, FCC part 15B Class A	
EMC	IEC61850-3/IEEE 1613: 2013 compliance for Power Substation EN50121-4 Compliance for Railway Roadside	
Safety	EN60950-1 Compliance *AC Power Source is UL approved.	
100Base FX		
Multi Mode	AVC-SFP-FX-SX (550m)	Wavelength: 850 nm
	AVC-SFP-FX-S (2km)	Wavelength: 1310 nm
Single Mode	AVC-SFP-FX-10 (10km)	Wavelength: 1310 nm
1000Base FX		
Multi Mode	AVC-SFP-SX (550m)	Wavelength: 850 nm
	AVC-SFP-LX-S (2km)	Wavelength: 1310 nm
Single Mode	AVC-SFP-LX-10 (10km)	Wavelength: 1310 nm

Function interface

System LED:


- Power, System & Ring status

24x 100/1000M RJ-45 with LED for Link status

4x 100/1000M Copper / 100/1000M SFP Fiber Combo with LED for Link Status Configured as

- 4 Copper or
- 4 Fiber or
- 2 Copper and 2 Fiber

4x 100/1000M SFP Fiber with LED for Link status



- 1xDigital Input
- 1xDigital Output

Console, USB for management


Power 1 AC Power or DC Power

Power 2 AC Power or DC Power



Installation dimensions

Unit: mm



AVCOMM Technologies, Inc. All rights reserved. Trademarks and trade names that may be used in this document are owned by their respective companies. Specifications subject to change without notice. Please ask our sales for the most up-to-date product information. Avcomm Technologies Inc. Add: 333 West Loop North Ste. 460, Houston, TX 77024