



AVC-A420-2A420

Datasheet

Aiming to create better and safer working environments and life experiences through the products we deliver.



AVCOMM Technologies, Inc

www.avcomm.us

Email: info@avcomm.us

Phone: (713) 933-4534

Address: 333 West Loop North, Suite 460
Houston, TX 77024
United States

Signal Splitter

AVC-A420-2A420

AVCOMM AVC-A420-2A420 is 2, 3, 4-wire universal distributor. It has power indicator, alarm status indicator. Input and output signals can be configured, and the input/output/power channels are fully isolated. The base is centrally powered and support hot swap.



Ordering Information

Model Name	Description
AVC-A420-2A420-D	1 x 4-20mA input, 2 x 4-20mA output, DC24V

Specification

Technology	
Distribution voltage	24VDC (Maximum driving current 40mA)
Output load	0-350Ω
Response time	< 0.05s (0 ~ 90%) (TYP)
Ripple	< 10mVrms
Transmission error	The final value of 0.1%
Temperature coefficient	50ppm/K measurement /100Ω load
Insulation impedance	500VDC is greater than 100MΩ
Compressive strength	1500VAC/min
EMC compatibility	compliant with IEC61326-1
Base index	Rated voltage: DC24V, Rated current: DC5A
	Maximum voltage: DC30V
	Pressure tolerance between gold fingers: DC1500V
Power supply	24VDC±25% (Power reverse protection)
Power consumption	< 1.5W
Mechanical & Environmental	
Enclosure Material	ABS flame retardant
Dimension	Terminal power supply : Thickness 13.3 x width 108 x height 110 (mm) Base power supply: Thickness 13.3 x width 113 x height 121 (mm)
Weight	~120g
Working temperature	-20°C ~ + 60°C
Working humidity	< 90% RH, Non- Condensing
Warranty	2 years

AVCOMM Technologies, Inc. All rights reserved. Trademarks and trade names that may be used in this document are owned by their respective companies. Specifications subject to change without notice. Please ask our sales for the most up-to-date product information. Avcomm Technologies Inc. Add: 333 West Loop North Ste. 460, Houston, TX 77024

Wiring Diagram

